







LED HIGHBAY

LITEBAY

Our market research indicated a high demand for a suitable alternative to the Aqualuma premium Highbay range. To facilitate this need Aqualuma has developed the Litebay, an Australian made and warrantied Highbay. The Litebay has been created with the same quality and ingenuity Aqualuma is renowned for, but at a very competitive price. The 150W Litebay produces an impressive 19,245 lumen's providing an ideal light for light replacement solution for the commercial & industrial sector.

Specifications

| LED Light Source | Lumileds | |
|-------------------|---------------------------|-----------------|
| Colour Temp (Tc) | 5000 Kelvin | |
| CRI | CRI > 80 | |
| Lens Options | Clear Acrylic | Diffuse Acrylic |
| Luminous Flux | 19,245lm (129lm/w) | 18,629lm |
| LED Current / LED | 150W | |
| Input Voltage | 90V-277V 47-63Hz | |
| Warranty | 7 year | |
| Lens Options | Clear or diffused acrylic | |

Features

- One for one replacement for 400W metal halide light fittings
- Output flux 19,245 lm
- Luminaire efficacy up to 129 lm/W
- Full spectrum colour rendering (improved visual acuity in comparison to metal halide and fluorescent light fittings)
- LM6 marine grade aluminium / powder coated
- Certified to all applicable AS/NZ standards
- Instant on / off
- Sensor options available
- IP66 rated
- Flicker free

Electrical Specifications

Operating voltage: 90-277VAC, 47-63Hz

Power factor: $\lambda > 0.99$

Operating Temperature: -40 ° C to 45 ° C

Mechanical Information

Weight: 7.5kg

Mounting: Eye, bracket, ceiling plate, ezystrut

Cabling: 3m PVC cable + 3 pin plug (std)

Housing: Marine grade powder coated "copper

free" aluminium

Lens: Clear or diffused acrylic

















