



AQUALUMA®
LED LIGHTING



**VEET & IPART
APPROVED**

**5
YEAR
WARRANTY**



HACCP LED CANOPY LIGHT


The Aqualuma HACCP Certified LED Canopy Light has been designed for both new builds and retro fitting into food processing facilities, commercial cold stores, fuel station forecourts, and other canopy roofs. The Canopy light allows for ease of installation and can be surface mounted on multiple ceiling types including concrete or sandwich panel. The slim low-profile design requires very low maintenance and continues Aqualuma's renowned product reliability and energy efficiency.

SPECIFICATIONS

LED Light Source	Lumileds
Colour Temp (Tc)	5000 Kelvin
CRI	CRI 75
Luminous Flux	from 13,500lm to 23,095lm
LED Current / LED	90W, 125W, 165W
Input Voltage	90V-277V 47-63Hz
Warranty	5 year
Lens Options	Clear or Diffuse
Control Options	Intelligent control options available
Mounting Options	Surface mount or with stand off frame

TECHNICAL SPECIFICATIONS

- Provides lighting for food preparation facilities, commercial cold stores and service station forecourts
- 90W, 125W & 165W versions available
- Output flux from 13,500lm to 23,095lm
- Luminaire efficacy up to 150lm/W
- 6063 T5 aluminium, white powder coated and ABS componentry
- 5 year warranty
- Instant on / off
- Food Grade certification
- IP65 rated
- IPART and VEET approved
- Flicker free



ISO 9001:2015 CERTIFIED



VEET & IPART
APPROVED

5
YEAR
WARRANTY



AQUALUMA®
LED LIGHTING



MECHANICAL INFORMATION

Weight: Slimline=6.5kg / with stand off frame=8kg

Mounting: Surface mount or with stand off frame

Cabling: 1.5m cable rated to -40 °C to 75 °C (std)

Housing: 6063 T5 aluminium, white powder coated and polycarbonate componentry

Lens: Impact resistant acrylic (standard), Polycarbonate

ELECTRICAL SPECIFICATIONS

Operating voltage: 90-277VAC, 47-63Hz

Power factor: $\lambda > 0.96$

Operating Temperature: -40 °C to 45 °C

